



AFTEC Cable Markers are ECM TYPE Flexible PVC Markers for Cables between 1.0 mm to 25mm diameter suitable for all types of Industrial and Electrical Applications.

AFTEC Cable Markers are made of Soft PVC in Concave Convex shape and number coded with the following markings.

0-9, A-Z, + (plus), (-) Minus, Oblique, Earth, Blank.

Aftec Cable Markers have operational service temperature of -40°C to +85°C.

Aftec Cable markers are Resistant to Sea Water, Detergents, Fuels, Oils and Spirits and are Erosion Controlled.

AFTEC Cable Markers are suitable for any Size, Any Special Lengths and the inside are hollow and elastic.

## CABLE MARKER

Aftec cable markers are flexible pvc marker for cables between 0.5mm<sup>2</sup> to 10mm<sup>2</sup>. Chevron cut design ensures that markers stay locked to each other and doesn't allow to rotate and maintain entire identification in one line.

### Technical Data

Application : For wire identification in electrical & electronic wires and are resistant to sea water, detergents, fuels, oil and spirits.

Material : Soft P.V.C

Temperature range : - 40°C to +85°C.

Color : Yellow & White with Black marking.

Marking : 0-9, A-Z, + (Plus), - (Minus), / (Oblique), (Earth) ⊥ Blank.

### Z-TYPE CABLE MARKERS

| MODEL NO | WIRE SIZE       | IN DIAMETER | LENGTH | MARKERS                 | PACKING/BOX |
|----------|-----------------|-------------|--------|-------------------------|-------------|
|          | mm <sup>2</sup> | MM          | MM     |                         |             |
| ACM 0    | 0.5 to 0.75     | 1.8 to 2.2  | 6712   | A to Z, 0-9, +, -, /, ⊥ | 1500 Nos    |
| ACM 1    | 1.0 to 2.5      | 3.2 to 3.8  | 4445   | A to Z, 0-9, +, -, /, ⊥ | 1000 Nos    |
| ACM 2    | 2.5 to 6.0      | 4.5 to 5.2  | 2810   | A to Z, 0-9, +, -, /, ⊥ | 500 Nos     |
| ACM 3    | 6.0 to 10.0     | 5.5 to 6.8  | 1830   | A to Z, 0-9, +, -, /, ⊥ | 350 Nos     |

### K-TYPE CABLE MARKERS

| MODEL NO | WIRE SIZE       | IN DIAMETER | LENGTH | MARKERS                 | PACKING/BOX |
|----------|-----------------|-------------|--------|-------------------------|-------------|
|          | mm <sup>2</sup> | MM          | MM     |                         |             |
| ACM K    | 4.0 to 10.0     | 4.0 to 7.0  | 2650   | A to Z, 0-9, +, -, /, ⊥ | 500 Nos     |

## CARRIER STRIPS

Aftec Carrier strips are used with ties up to width of 4.8 mm

### Technical Data

Application : To mark cable bundles for permanent identification with aftec k type cable marker

Material : Nylon

Temperature range : - 40°C to +85°C.

Color : Black

| MODEL NO. | WIDTH | LENGTH |     | MAX CAPACITY<br>MARKERS PER STRIP | STANDERED<br>QUANTITY<br>PER BAG |
|-----------|-------|--------|-----|-----------------------------------|----------------------------------|
|           | W     | L      |     |                                   |                                  |
|           | MM    | INCH   | MM  |                                   |                                  |
| AMS 65    | 9     | 2.6    | 65  | 7                                 | 100                              |
| AMS100    | 9     | 4.0    | 100 | 12                                |                                  |
| AMS 135   | 9     | 5.4    | 135 | 18                                |                                  |